

TILEPASTE

Super High Quality Tile Adhesive



General Properties:

- **TILEPASTE** is ready to use paste used for direct application as tile adhesive over, wood, gypsum, cement or any porous substrata.
- Good elasticity.
- High adhesion to gypsum & wood partitions, cement, fair face concrete, or render.

Preparation of Surface:

١. Clean surface & remove all loose particles & foreign materials.
٢. Insure that the surface is leveled.

Application:

١. Mix **TILEPASTE** in the container before use.
٢. Using one side notched trowel apply a layer with the required thickness to the surface.
٣. Be sure that the thickness of the adhesive suits the weight of the tile.
٤. Twist while pressing the tile on the adhesive layer till you ensure complete adhesion.
٥. The applied layer should be suitable for fixing up tiles before maximum ٢٠ min. Do not leave **TILEPASTE** uncovered in the container for a long time to prevent the formation of a skin layer.
٦. Clean tools after application using water.
٧. Use a wet sponge for cleaning the tiles.
٨. Grout tile joints recommended **TILEGROUT**.

Technical Data:

Bonding agent	: modified synthetic resin.
Initial Drying	: From ٢-٥ hours.
Density	: ١.٦٠ kg/liter.
Water Resistance	: Excellent.
Consumption	: ٢ – ٣ kg / m ^٢ (depends on substrate roughness and tile dimensions).
Shelf Life	: ١٢ months in closed container and away from sunlight, heat and humidity.

Environment:

- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: ٢١ Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel: ٠٠٢ / ٠٢ ٢٤٥٣٥٦٧٨ - ٢٤٥٣٥٦٧٩ Fax: ٠٠٢ / ٠٢ ٢٤٥٣٨٩٨٦
 Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com